



TAKT: COUNTS DOWN FROM SET START TIME. AT ZERO, RESETS TO START AND COUNTS DOWN AGAIN
GOAL: AUTOMATICALLY INCREASES WHEN TAKT TIME = 0
ACTUAL: MANUAL COUNT UP VIA UP/DOWN SWITCHBOX OR VIA DRY CONTACT(OPTIONAL)

BPCN-49940-3-IRR-BOX-USB-ETHR

SPECIFICATIONS

- TYPE:**----- DIGITAL
- DISPLAY:**----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
- CHARACTER HEIGHT:**----- 4" (101.6 mm) 9 THOUSAND 9 HUNDRED AND 99; 99 MIN AND 59 SEC
- VISIBILITY:**----- 250 Ft. (76.2 METERS)
- POWER REQUIREMENTS:** 100-240V 50~60Hz (**SWITCHING POWER SUPPLY**)
- FRAME:**----- 18.25" x 30.25" x 1.5" (**Black Anodized Aluminum**)
- WEIGHT:**----- 11 lbs.
- OPERATING TEMP.:**----- -17° TO 182° F
- HUMIDITY:**----- 0% TO 95% NON-CONDENSING
- OPERATING MODE** ----- ACTUAL COUNT UP BY 1 VIA 15 FT SWITCH BOX. GOAL AUTOMATICALLY INCREASES BY 1 VIA TAKT TIMER WITH RUN/HOLD AND RESET CONTROL; USB TO PC CONNECTION AND ETHERNET CONNECTION FOR WEB-BASED INTERFACE FOR HISTORICAL DATA

